

CORTADOR ANULAR DE ACERO ALTA VELOCIDAD

- Gran durabilidad
- Zanco tipo Weldon de 3/4"*
- Fabricado en acero alta velocidad
- Capacidad de perforación superior

CÓDIGO	DIÁMETRO	PROFUNDIDAD DE CORTE	FLAUTAS
ST-5-530-111	1/2" (12.7mm)	1" (25.4mm)	4
ST-5-530-113	9/16" (14.28mm)	1" (25.4mm)	4
ST-5-530-116	5/8" (15.87mm)	1" (25.4mm)	5
ST-5-530-119	11/16" (17.46mm)	1" (25.4mm)	5
ST-5-530-121	3/4" (19.05mm)	1" (25.4mm)	6
ST-5-530-124	13/16" (20.63mm)	1" (25.4mm)	6
ST-5-530-127	7/8" (22.22mm)	1" (25.4mm)	6
ST-5-530-133	1" (25.4mm)	1" (25.4mm)	6
ST-5-530-136	1-1/16" (26.98mm)	1" (25.4mm)	8
ST-5-530-145	1-1/4" (31.75mm)	1" (25.4mm)	8
ST-5-530-160	2-5/8" (66.67mm)	1" (25.4mm)	14
ST-5-530-211	1/2" (12.7mm)	2" (50.8mm)	4
ST-5-530-213	9/16" (14.28mm)	2" (50.8mm)	4
ST-5-530-216	5/8" (15.87mm)	2" (50.8mm)	5
ST-5-530-218	11/16" (17.46mm)	2" (50.8mm)	5
ST-5-530-221	3/4" (19.05mm)	2" (50.8mm)	6
ST-5-530-227	7/8" (22.22mm)	2" (50.8mm)	6
ST-5-530-229	15/16" (23.81mm)	2" (50.8mm)	6
ST-5-530-233	1" (25.4mm)	2" (50.8mm)	6
ST-5-530-237	1-1/16" (26.98mm)	2" (50.8mm)	8
ST-5-530-239	1-1/8" (28.57mm)	2" (50.8mm)	8
ST-5-530-242	1-3/16" (30.16mm)	2" (50.8mm)	8
ST-5-530-245	1-1/4" (31.75mm)	2" (50.8mm)	8
ST-5-530-248	1-5/16" (33.33mm)	2" (50.8mm)	8
ST-5-530-251	1-3/8" (34.92mm)	2" (50.8mm)	10
ST-5-530-257	1-1/2" (38.1mm)	2" (50.8mm)	10
ST-5-530-260	1-9/16" (39.68mm)	2" (50.8mm)	10
ST-5-530-263	1-5/8" (41.27mm)	2" (50.8mm)	10
ST-5-530-269	1-3/4" (44.45mm)	2" (50.8mm)	10
ST-5-530-275	1-7/8" (47.62mm)	2" (50.8mm)	10
ST-5-530-281	2" (50.8mm)	2" (50.8mm)	12

(Excepto código ST-5-530-160 que es de 1-1/4")



- Perno botador disponibles
ST-5-530-905 1/4" X 3"
ST-5-530-915 1/4" X 4"